


Drain body The Universal DN 100, AISI304 grat., Backwater protect





Article information

Item no.: 27621

GTIN: 4026092007839

Price group: 10

Advantages

- Flexible installation: vertically adjustable upper section rotatable
- Integrated backwater protection
- vertically adjustable

Description

The polymer drain body is equipped with a removable backwater valve with two backwater flaps, one hand-lockable emergency closure and a sludge bucket. The drain body also has two inlets DN 50 and one inlet DN 70 with blind plug. Material:

PP

Variant

Contents of sludge trap: yes Emergency closure: yes

Waterproof flange: Pre-assembled at the factory

Mechanical backwater flaps: 2

General characteristics

Colour: black

Standard: EN 1253, EN 13564

Nominal size (DN): 100 Outer diameter (OD): 110 mm

Type of wastewater: without sewage Installation situation: floor slab installation Delivery state: installation-ready

Backwater protection: Type 5
ATEX: no
Odour trap: included



Dimensions

Net weight:3,23 kgGross weight:3,55 kgCutout dimension, width:320 mmCutout dimension, length:400 mmInstallation depth:216 - 266 mm

Type of height adjustability: vertically adjustable upper section

Length:380 mmWidth:300 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Socket version: lateral

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover: silver

Load class: K 3 (EN 1253-1)

Grid size, length: 187 mm
Grid size, width: 187 mm
Grid size, height: 4 mm
Contents of sludge trap: yes

Cover

Grid size, length: 187 mm
Grid size, width: 187 mm
Grid size, height: 4 mm