


## Aquadive GTF 500 submersible pump with float switch, 10 m





## Article information

Item no.: 280810 GTIN: 4026092082515 Price group: 20

## **Advantages**

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

## Description

Submersible pump GTF 500 for faecal-free wastewater

- housing made of polymer/stainless steel
- with longitudinally watertight, moulded connection cable
- with float switch for level measurement
- with removable intake cage and carry handle
- with vertical pressure pipe connection
- with multi-vane impeller for maximum operating reliability
- with integrated low-level suction

Variant	
Pump control:	Float switch
Pressure pipe connection:	vertical
General characteristics	
Material:	Polymer
Standard:	EN 12050-2
Type of wastewater:	without sewage
Cable length:	10 m
ATEX:	no
Dimensions	
Net weight:	6,09 kg



Gross weight: Length: Width: Height: Packaging dimension: Packaging dimension: Packaging dimension:	6,97 kg 185 mm 120 mm 220 mm length width height
Wastewater contents Pressure pipe connection:	R 1 ¼ "
Pumping device Pump: Number of pumps: Weight, pump: Connection type: Rated current: Protection class: Insulation class: Cos phi - power factor: Protection class (pump): Temperature monitoring: Max. temperature (permanent) of conveyed	GTF 500 1 6 kg Schuko (earthed contact) 2-pin 2,5 A I F 0,91 IP 68 (3m) integrated 40 °C
material: Hot water resistance for a short time (2 min): Max. pumping height: Speed: Power P1: Power P2: Operating mode: Type of fuse required (electrical protection): Type of fuse required (electrical protection): Type of pump connection cable: Impeller type: Free passage: Length of mains cable for pump:	80 °C 8 m 2800 U/min 0,5 kW 0,36 kW S1 C 16 A H07RN-F 3G 1.5 mm² Multi-vane impeller 10 mm 10 m
Control Type of level measurement: Mains frequency: Operating voltage: Connection type: Type of fuse required (electrical protection):	mechanical 50 Hz 230 V Schuko (earthed contact) 2-pin C 16 A