

Replacement pump KTP 300 for Minilift



Article information

Item no.: 28836
 GTIN: 4026092000922
 Price group: 90

Description

Variant	
Pump control:	Float switch
General characteristics	
Standard:	EN 12050-2
Type of wastewater:	without sewage
Cable length:	5 m
Dimensions	
Net weight:	4,21 kg
Gross weight:	4,49 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	KTP 300
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	1,9 A
Length of mains cable for pump:	5 m
Protection class:	I
Insulation class:	F
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	35 °C
Max. pumping height:	6 m
Speed:	2800 U/min
Power P1:	0,34 kW
Power P2:	0,21 kW
Operating mode:	S1
Type of fuse required (electrical protection):	C 16 A

Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Control	
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	1,9 A