


Submersible pump Aquadive GTF1000 with float switch, 10m



Article information

Item no.: 28860
 GTIN: 4026092044513
 Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

Submersible pump for faecal-free wastewater, type KTP 1000, new designation: **GTF 1000**

Variant
 Pump control: **Float switch**

General characteristics
 Material: **Polymer**
 Standard: **EN 12050-2**
 Type of wastewater: **without sewage**
 Cable length: **10 m**
 ATEX: **no**

Dimensions
 Net weight: **10 kg**
 Gross weight: **11,19 kg**
 Length: **195 mm**
 Width: **195 mm**
 Height: **290 mm**
 Packaging dimension: **length**
 Packaging dimension: **width**
 Packaging dimension: **height**

Wastewater contents	
Pressure pipe connection:	R 1 ¼"
Pumping device	
Pump:	GTF 1000
Number of pumps:	1
Weight, pump:	10 kg
Connection type:	coded plug
Rated current:	5,6 A
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,97
Protection class (pump):	IP 68 (3m)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	10 m
Speed:	2700 U/min
Power P1:	1,3 kW
Power P2:	0,75 kW
Operating mode:	S3 - 50 %
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Length of mains cable for pump:	10 m
Control	
Type of level measurement:	mechanical
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	coded plug
Type of fuse required (electrical protection):	C 16 A