


Universal Plus basement drain ver., odour trap, Waterproof concrete





Article information

Item no.: 29102

GTIN: 4026092096956

Price group: 10

Advantages

- Sustainable due to use of recycled material
- Inlets above the floor slab, no penetration required
- Vertical outlet for easy installation and easy access to the main drainage pipe

Description

In combination with an upper section, the polymer Universal Plus drain body is used for drainage of non-faecal wastewater and is equipped with a removable odour trap and a sludge bucket. Including temporary protective cover. The drain is pressure-waterproof up to 0.6 bar (MFPA Leipzig tested) and radon-tight (IAF Radioökologie GmbH tested).

Variant

Contents of sludge trap: yes

Waterproof flange: Pre-assembled at the factory

Sealing water height: 60 mm

General characteristics

Colour: black
Standard: EN 1253
Nominal size (DN): 100

Type of wastewater: without sewage Installation situation: floor slab installation

ATEX: no Odour trap: included

Dimensions

Net weight: 2,38 kg Gross weight: 2,79 kg



Diameter: 295 mm
Cutout dimension, width: 310 mm
Cutout dimension, length: 310 mm

Type of height adjustability: vertically adjustable upper section

Height: 270 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Outlet nominal size (OD):110 mmOutlet nominal size (DN):100 mmSocket version:vertical

Coverage features

Contents of sludge trap: yes