

Basement drain DN 100, Black grating, Class K 3



Article information

Item no.: 29111

GTIN: 4026092007846

Price group: 10

Advantages

- Integrated odour trap
- Including sludge bucket

Description

The basement drain made of polymer for floor slab installation is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap:

Position of lateral connection:

Sealing water height:

Discharge rate (l/s) with 20 mm threshold:

yes

Type II

60 mm

General characteristics

Standard: EN 1253-1
Nominal size (DN): 100
Outer diameter (OD): 110 mm
Odour trap: included

Dimensions

Vertical adjustment:30 - 90 mmNet weight:2,55 kgGross weight:2,88 kgCutout dimension, width:320 mmCutout dimension, length:400 mmInstallation depth:216 - 276 mm

Type of height adjustability: vertically adjustable upper section

Length: 380 mm
Width: 290 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Inlet nominal size (DN): 70 mm



Number of inlets: 2
Material of drain body: PP
Socket version: lateral

Coverage features

Type of cover:

Cover material:

Polymer

Colour of cover:

black

Width of cover:

188 mm

Length of cover:

188 mm

Frame material:

Polymer

Locking:

placed

Load class:K 3 (EN 1253-1)Rim width:200 mmRim length:200 mmUpper section material:PolymerContents of sludge trap:yes