

Roof drain Press. fl., DN 100, with leaf trap



Article information

Item no.: 45950 GTIN: 4026092001318 Price group: 10

Description

Variant

The roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. Note: Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

System: Heating: Waterproofing layer on the drain body:	100 without Press sealing flange (suitable for creating watertight seals)
General characteristics	
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Dimensions	
Net weight:	0,92 kg
Gross weight:	1,11 kg
Diameter:	246 mm
Cutout dimension, width:	180 mm
Cutout dimension, length:	180 mm
Length:	246 mm
Width:	246 mm
Height:	182 mm
Packaging dimension:	length
Packaging dimension:	width

Tank/drain body

Packaging dimension:

height



Material of drain body:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Height of cover: Length of cover: Shape of upper section: Upper section material: PP

Leaf trap Polymer black 120 mm 80 mm 120 mm round PP