

Upper section, Linearis Compact L: 750mm, Sys 100, 304 SST cover, K 3



Article information

Item no.: 47808S GTIN: 4026092077818 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

Description

Used in combination with a drain body of the KESSEL 100 modular system, the Linearis Compact upper section is suitable for use as indoor linear drainage.

System:100Seepage opening:yesWaterproofing layer on the upper section:Enclosed sealing collar to be glued (bd) according to DIN 18534Water exposure class in accordance to DIN 18534-1 (up to and including):W3-1Sealing water height:50 mmDischarge rate (l/s) with 10 mm threshold:0,6Discharge rate (l/s) without threshold:0,5 mmGeneral characteristics0,5 mmNominal size (DN):100Outer diameter (OD):100 mmATEX:noOdour trap:includedDimensions1,79 kgGross weight:2,55 kgOuter dimension, length:80 - 140 mm	Variant	
Waterproofing layer on the upper section:Enclosed sealing collar to be glued (bd) according to DIN 18534Water exposure class in accordance to DIN 18534-1 (up to and including): Sealing water height:W3-1Sealing water height:50 mmDischarge rate (I/s) with 10 mm threshold:0,6Discharge rate (I/s) without threshold:0,5 mmGeneral characteristics Nominal size (DN):100Outer diameter (OD):100 mmATEX:noOdour trap:includedDimensions Net weight:1,79 kgGross weight:2,55 kgOuter dimension, length:815 mm	System:	100
DIN 18534Water exposure class in accordance to DINW3-I18534-1 (up to and including): Sealing water height:50 mmDischarge rate (l/s) with 10 mm threshold:0,6Discharge rate (l/s) without threshold:0,5 mmGeneral characteristics Nominal size (DN):100Outer diameter (OD):100 mmATEX:noOdour trap:includedDimensions Net weight:1,79 kgGross weight:2,55 kgOuter dimension, length:815 mm	Seepage opening:	yes
18534-1 (up to and including):Sealing water height:50 mmDischarge rate (l/s) with 10 mm threshold:0,6Discharge rate (l/s) without threshold:0,5 mmGeneral characteristicsNominal size (DN):100Outer diameter (OD):100 mmATEX:noOdour trap:includedDimensionsNet weight:1,79 kgGross weight:2,55 kgOuter dimension, length:815 mm	Waterproofing layer on the upper section:	
Discharge rate (l/s) with 10 mm threshold:0,6Discharge rate (l/s) without threshold:0,5 mmGeneral characteristics0,5 mmNominal size (DN):100Outer diameter (OD):100 mmATEX:noOdour trap:includedDimensions	•	W3-I
Discharge rate (l/s) without threshold:0,5 mmGeneral characteristicsNominal size (DN):0uter diameter (0D):100 mmATEX:noOdour trap:DimensionsNet weight:Net weight:0uter dimension, length:815 mm	Sealing water height:	50 mm
General characteristicsNominal size (DN):100Outer diameter (OD):100 mmATEX:noOdour trap:includedDimensionsNet weight:1,79 kgGross weight:2,55 kgOuter dimension, length:815 mm	Discharge rate (l/s) with 10 mm threshold:	0,6
Nominal size (DN):100Outer diameter (OD):100 mmATEX:noOdour trap:includedDimensionsNet weight:1,79 kgGross weight:2,55 kgOuter dimension, length:815 mm	Discharge rate (l/s) without threshold:	0,5 mm
Nominal size (DN):100Outer diameter (OD):100 mmATEX:noOdour trap:includedDimensionsNet weight:1,79 kgGross weight:2,55 kgOuter dimension, length:815 mm		
Outer diameter (0D):100 mmATEX:noOdour trap:includedDimensions	General characteristics	
ATEX:noOdour trap:includedDimensions	Nominal size (DN):	100
Odour trap:includedDimensions	Outer diameter (OD):	100 mm
DimensionsNet weight:1,79 kgGross weight:2,55 kgOuter dimension, length:815 mm	ATEX:	NO
Net weight:1,79 kgGross weight:2,55 kgOuter dimension, length:815 mm	Odour trap:	included
Net weight:1,79 kgGross weight:2,55 kgOuter dimension, length:815 mm		
Gross weight:2,55 kgOuter dimension, length:815 mm	Dimensions	
Outer dimension, length: 815 mm	Net weight:	1,79 kg
	Gross weight:	2,55 kg
Installation depth: 80 - 140 mm	Outer dimension, length:	815 mm
	Installation depth:	80 - 140 mm
Width: 136 mm	Width:	136 mm
Height: 77 mm	Height:	77 mm
Packaging dimension: length	Packaging dimension:	length
Packaging dimension: width	Packaging dimension:	width



Packaging dimension:

Coverage features Type of cover: Cover material: Colour of cover: Frame material: Load class: Grating design: Rim width: Rim length: Upper section material:

height

Stainless steel cover Stainless steel 14301 silver Stainless steel 14301 K 3 (EN 1253-1) optionally tileable 66 mm 750 mm ABS