

## Linearis Comfort upper section L: 1150 mm, System 125, WaD, K 3



## **Article information**

Item no.: 48932M GTIN: 4026092079089

Price group: 10

## **Advantages**

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

## **Description**

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

Variant

System: 125 Seepage opening: open

Waterproofing layer on the upper section: Factory-fitted sealing collar (WaD) according to DIN

18534 W3-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height: 50 mm
Discharge rate (l/s) with 10 mm backwater: 1,1
Discharge rate (l/s) without backwater: 1 mm

General characteristics

Nominal size (DN): 125
Outer diameter (OD): 125 mm
ATEX: no
Odour trap: included

**Dimensions** 

Net weight: 4,55 kg Gross weight: 5,26 kg Outer dimension, length: 1215 mm Installation depth: 80 - 140 mm Width: 243 mm 107 mm Height: Packaging dimension: length Packaging dimension: width Packaging dimension: height



Coverage features

Type of cover: Stainless steel cover Cover material: Stainless steel 14301

Colour of cover: silver

Surface: Brushed SST

Frame material: Stainless steel 14301

Locking: placed

Load class: K 3 (EN 1253-1)
Grating design: optionally tileable

Rim width: 66 mm
Rim length: 1150 mm
Shape of upper section: square
Upper section material: ABS