

Replacement pump Aquadive SPF1300 230 V



Article information

Item no.: 680535
 GTIN: 4026092075012
 Price group: 90

Description

Replacement pump, Aquadive, SPF 1300 for faecal wastewater

Variant

Pump control: Control unit

General characteristics

Type of wastewater: with sewage
 Cable length: 5 m

Dimensions

Net weight: 9,39 kg
 Gross weight: 10,3 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: SPF 1300
 Number of pumps: 1
 Weight: 10 kg
 Connection type: Direct connection
 Rated current: 6,4 A
 Length of mains cable for pump: 5 m
 Protection class: I
 Insulation class: F
 Cos phi - power factor: 0,98
 Protection class (pump): IP 68
 Temperature monitoring: integrated
 Max. temperature (permanent) of conveyed material: 35 °C
 Max. pumping height: 9,2 m
 Speed: 2600 U/min
 Power P1: 1,5 kW

Power P2: 0,91 kW
Operating mode: S3 - 10 %
Type of pump connection cable: H07RN-F 3G 1.5 mm²

Control

Mains frequency: 50 Hz
Operating voltage: 230 V
Connection type: Direct connection
Rated current: 6,4 A