

Replacement pump Aquadive SPF1300 230 V



Article information

Item no.: 680535 GTIN: 4026092075012

Price group: 90

Description

Replacement pump, Aquadive, SPF 1300 for faecal wastewater

Variant

Pump control: Control unit

General characteristics

Type of wastewater: with sewage

Cable length: 5 m ATEX: no

Dimensions

Net weight:9,39 kgGross weight:10,3 kgPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Pumping device

Pump: SPF 1300

Number of pumps: 1
Weight, pump: 10 kg

Connection type: Direct connection

Operating voltage: 230 V
Mains frequency: 50 Hz
Rated current: 6,4 A
Protection class: I
Insulation class: F
Cos phi - power factor: 0,98
Protection class (pump): IP 68

Temperature monitoring: integrated Max. temperature (permanent) of conveyed $35 \,^{\circ}$ C

material:

Max. pumping height: 9,2 m



 Speed:
 2600 U/min

 Power P1:
 1,5 kW

 Power P2:
 0,91 kW

 Operating mode:
 \$3 - 10 %

Type of pump connection cable: H07RN-F 3G 1.5 mm²

Length of mains cable for pump: 5 m

Control

Connection type: Direct connection