

## Replacement pump Aquadive GTF1200 without float switch, 10 m



### Article information

Item no.: 680595  
 GTIN: 4026092078815  
 Price group: 90

### Description

Replacement pump, Aquadive GTF 1200 without floater for pumping station

#### Variant

Pump control: Control unit

#### General characteristics

Cable length: 10 m

#### Dimensions

Net weight: 11,19 kg

Gross weight: 11,19 kg

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

#### Pumping device

Pump: GTF 1200

Connection type: Schuko (earthed contact) 2-pin

Rated current: 6,2 A

Length of mains cable for pump: 5 m

Protection class: I

Insulation class: F

Cos phi - power factor: 0,98

Protection class (pump): IP 68

Temperature monitoring: integrated

Max. temperature (permanent) of conveyed material: 35 °C

Max. pumping height: 9 m

Speed: 2650 U/min

Power P1: 1,4 kW

Power P2: 0,84 kW

Operating mode: S1

Type of fuse required (electrical protection): Fuse protection through control unit 230 V

Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Control	
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	6,2 A