

Replacement pump Aquadive STZ3700 without float switch, 10 m, ATEX



Article information

Item no.: 680606
GTIN: 4026092078501
Price group: 90

Description

Replacement pump, Aquadive, STZ 3700, ATEX, without floater, for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m
ATEX: yes

Dimensions

Net weight: 43 kg
Gross weight: 46 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: STZ 3700
Weight, pump: 44 kg
Connection type: Direct connection
Operating voltage: 400 V
Mains frequency: 50 Hz
Rated current: 6,4 A
Protection class: I
Insulation class: H
Cos phi - power factor: 0,82
Protection class (pump): IP 68
Temperature monitoring: controlled via control unit
Max. temperature (permanent) of conveyed material: 40 °C

Max. pumping height:	35 m
Speed:	2900 U/min
Power P1:	3,7 kW
Power P2:	3,1 kW
Operating mode:	S1
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V
Type of pump connection cable:	H07RN8-F 6G 1.5 mm ²
Impeller type:	Macerator
Length of mains cable for pump:	10 m
Control	
Connection type:	Direct connection
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V