

## Replacement pump KTP 300 res., Minilift S, free-standing set-up



### Article information

Item no.: 680954  
GTIN: 4026092093818  
Price group: 90

### Description

Replacement pump resistant to salty media, wastewater from water softening systems and wastewater containing condensate from heating systems.

#### General characteristics

ATEX: no

#### Dimensions

Net weight: 4,48 kg  
Gross weight: 4,48 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Pumping device

Pump: KTP 300  
Connection type: Schuko (earthed contact) 2-pin  
Operating voltage: 230 V  
Mains frequency: 50 Hz  
Rated current: 1,9 A  
Protection class: I  
Protection class (pump): IP 68 (3m)  
Max. temperature (permanent) of conveyed material: 35 °C  
Max. pumping height: 6 m  
Speed: 2800 U/min  
Power P1: 0,34 kW  
Power P2: 0,21 kW  
Operating mode: S1  
Type of fuse required (electrical protection): C 16 A  
Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup>  
Length of mains cable for pump: 5 m

#### Control

Connection type:

Schuko (earthed contact) 2-pin

Type of fuse required (electrical protection):

C 16 A