

## Replacement pump GTF 600 w. float switch, Aqualift S 100/200, 5m



### Article information

Item no.: 680976  
GTIN: 4026092095898  
Price group: 90

### Description

Replacement pump with float switch for faecal-free wastewater.

#### Variant

Pump control: Float switch

#### General characteristics

Type of wastewater: without sewage

#### Dimensions

Net weight: 6,8 kg

Gross weight: 6,8 kg

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

#### Pumping device

Pump: GTF 600

Connection type: Schuko (earthed contact) 2-pin

Rated current: 2,9 A

Length of mains cable for pump: 5 m

Protection class (pump): IP 68 (3m)

Max. temperature (permanent) of conveyed material: 40 °C

Max. pumping height: 8 m

Speed: 2750 U/min

Power P1: 0,65 kW

Power P2: 0,4 kW

Operating mode: S1

Type of fuse required (electrical protection): C 16 A

Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup>

Impeller type: Multi-vane impeller

Control

Mains frequency:

50 Hz

Operating voltage:

230 V

Connection type:

Schuko (earthed contact) 2-pin

Rated current:

2,9 A