


Controlfix backwater tech. mod. DN 100, closed channel passage





Article information

Item no.: 851001 GTIN: 4026092079317 Price group: 60

Advantages

- Komfort: expensive living or useful space is not lost
- No system noises or unpleasant odours and soiling in the building
- Straightforward installation thanks to low weight of the combined engineering chamber modules and variable upper sections for adaptation to the ground level

Description

The backwater technical module is equipped with an integrated clean out Controlfix and access steps. Thanks to the modular KESSEL system, the clean out can easily be converted to a Staufix SWA Premium backwater valve, Staufix FKA or Pumpfix F backwater pumping station.

Variant Chamber system:	modular chamber
General characteristics	
Colour:	black
Material:	PE-HD
Type of wastewater:	with sewage
Installation situation:	underground installation
Delivery state:	Installation-ready (connection parts must be
Approval	connected on site)
Approval:	Z-42.1-527
Dimensions	
Net weight:	60 kg
Gross weight:	80 kg



Groundwater resistant from lower edge of base section:	3000 mm
Vertical drop between inlet and outlet:	9 mm
Width: Height:	1200 mm 520 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Channel: Tank width max.:	continuous channel 1390 mm
Distance from centre of outlet pipe to tank	267 mm
bottom:	
Distance from centre of inlet pipe to tank	277 mm
bottom:	
Number of outlets:	1
Outlet nominal size (DN):	100 mm
Inlet nominal size (DN):	100 mm
Number of inlets:	1
Clear width of tank (LW):	1000 mm