

Grease separat. EasyClean Modular free, NS 1, Standard, 2-part



Article information

Item no.: 93001 GTIN: 4026092030875 Price group: 60

Advantages

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant	
Chamber system:	two-piece chamber
Disposal variant:	Standard
Shredder-Mix-System:	no
Sludge bucket:	no
Nominal size (NS):	1,00
SonicControl:	no
Refill inlet in accordance with DIN 1988:	no
Type of disposal:	manual with suction hose
General characteristics Material: Installation situation: Delivery state:	PE free-standing installation Installation-ready (connection parts must be connected on site)
ATEX:	no
Dimensions Net weight: Gross weight: Height tank bottom up to centre section:	41,5 kg 51 kg 648 mm



Height centre section to top edge of tank: Set-up area, length: Set-up area, width: Set-up area, height: Packaging dimension: Packaging dimension: Packaging dimension:	340 mm 1100 mm 1012 mm 988 mm length width height
Tank/drain body Distance pipe bottom outlet to tank bottom: Distance pipe bottom inlet to tank bottom: Outlet nominal size (OD): Outlet nominal size (DN): Inlet nominal size (OD): Inlet nominal size (DN): Connection inlet/outlet sockets:	415 mm 485 mm 110 mm 100 mm 110 mm 100 mm PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Coverage features Type of cover: Cover material: Colour of cover: Locking: Tightness:	Cover Polymer black Quick-release closure odour-tight
Wastewater contents Separator contents: Total volume: Contents of sludge trap: Storage quantity of grease:	100 l 200 l 100 l 40 l
Control Control unit:	ΠΟ