

Grease separator EasyClean free NS 3, Standard, Inspection window



Article information

Item no.: 93003.21
 GTIN: 4026092063286
 Price group: 60

Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

| | |
|---|--------------------------|
| Disposal variant: | Standard |
| Shredder-Mix-System: | no |
| Sludge bucket: | yes |
| Nominal size (NS): | 3 |
| SonicControl: | no |
| Refill inlet in accordance with DIN 1988: | no |
| Type of disposal: | manual with suction hose |
| Load-bearing capacity (DIN 19901): | F3 |

General characteristics

| | |
|-------------------------|---|
| Material: | PE |
| Installation situation: | free-standing installation |
| Delivery state: | Installation-ready (connection parts must be connected on site) |

Dimensions

| | |
|----------------------|----------|
| Net weight: | 87,5 kg |
| Gross weight: | 117,5 kg |
| Set-up area, length: | 1736 mm |
| Set-up area, width: | 674 mm |
| Set-up area, height: | 1434 mm |

| | |
|---|---|
| Required access area, length: | 1500 mm |
| Required access area, width: | 674 mm |
| Required access area, height: | 1434 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Tank/drain body | |
| Distance pipe bottom outlet to tank bottom: | 985 mm |
| Distance pipe bottom inlet to tank bottom: | 1055 mm |
| Outlet nominal size (OD): | 110 mm |
| Outlet nominal size (DN): | 100 mm |
| Inlet nominal size (OD): | 110 mm |
| Inlet nominal size (DN): | 100 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Coverage features | |
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | violet |
| Locking: | Quick-release closure |
| Tightness: | odour-tight |
| Wastewater contents | |
| Separator contents: | 300 l |
| Total volume: | 600 l |
| Contents of sludge trap: | 300 l |
| Storage quantity of grease: | 120 l |
| Control | |
| Control unit: | no |