


Grease separator EasyClean free NS 15, Standard, right





Article information

Item no.: 93015-01-R GTIN: 4026092105221

Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Direction of flow: right
Disposal variant: Standard
Shredder-Mix-System: no
Nominal size (NS): 15,00
SonicControl: no

Type of disposal: manual with suction hose

General characteristics

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

ATEX: no

Dimensions

Net weight: 355 kg



Gross weight: 430 kg Set-up area, length: 3530 mm Set-up area, width: 1680 mm Set-up area, height: 1950 mm Required access area, length: 3530 mm Required access area, width: 1490 mm Required access area, height: 1950 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

Outlet nominal size (DN):

Inlet nominal size (OD):

200 mm

Inlet nominal size (OD):

200 mm

Inlet nominal size (DN):

200 mm

Coverage features

Type of cover:

Cover material:

Colour of cover:

Tightness:

Cover

Polymer

violet

odour-tight

Wastewater contents

Separator contents:2230 lMax. grease layer thickness:180 mmTotal volume:3730 lContents of sludge trap:1500 lStorage quantity of grease:600 l