

EasyClean round grease separator free, NS 15, Direct

Article information

Item no.: 93015.05/D
 GTIN:
 Price group: 60

Advantages

- Odour-reduced disposal with the tank closed
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for reduced-odour manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

Variant

| | |
|---|---------------------|
| Shut-off valve: | yes |
| Disposal variant: | Direct |
| Shredder-Mix-System: | no |
| Sludge bucket: | no |
| Nominal size (NS): | 15 |
| SonicControl: | no |
| Disposal system: | Disposal connection |
| Refill inlet in accordance with DIN 1988: | no |
| Type of disposal: | manual |
| Load-bearing capacity (DIN 19901): | F3 |

General characteristics

| | |
|--------------------|---|
| Scope of delivery: | Storz-B coupling R 2 1/2" for disposal vehicle connection |
|--------------------|---|

Dimensions

| | |
|-------------------------------|---------|
| Net weight: | 350 kg |
| Gross weight: | 350 kg |
| Set-up area, length: | 2230 mm |
| Set-up area, width: | 1922 mm |
| Set-up area, height: | 2020 mm |
| Required access area, length: | 2230 mm |
| Required access area, width: | 1880 mm |
| Required access area, height: | 2020 mm |

Tank/drain body

| | |
|------------------------|----|
| Nominal pressure (PN): | 10 |
|------------------------|----|

| | |
|---|---|
| Pressure pipe connection (DN): | 65 |
| Pressure pipe connection (OD): | 75 mm |
| Distance pipe bottom outlet to tank bottom: | 1550 mm |
| Distance pipe bottom inlet to tank bottom: | 1620 mm |
| Outlet nominal size (OD): | 200 mm |
| Outlet nominal size (DN): | 200 mm |
| Inlet nominal size (OD): | 160 mm |
| Inlet nominal size (DN): | 150 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

Coverage features

| | |
|------------------|-----------------------|
| Type of cover: | Cover |
| Cover material: | Polymer |
| Colour of cover: | black |
| Locking: | Quick-release closure |
| Tightness: | odour-tight |

Wastewater contents

| | |
|-----------------------------|--------|
| Separator contents: | 2300 l |
| Total volume: | 3800 l |
| Contents of sludge trap: | 1500 l |
| Storage quantity of grease: | 600 l |

Control

| | |
|---------------|----|
| Control unit: | no |
|---------------|----|