

Grease separator EasyClean free NS 50, Standard

Article information

Advantages

Item no.: 93050.01 GTIN: 4026092103791 Can be retrofitted up to Auto Mix & PumpLow-maintenance operation

Price group: 60

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Disposal variant:

Shredder-Mix-System:

no
Sludge bucket:

no
Nominal size (NS):

SonicControl:

Refill inlet in accordance with DIN 1988:

Standard

no
no

Type of disposal: manual with suction hose

Load-bearing capacity (DIN 19901): F3

General characteristics

Material: PE Standard: EN 1825

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Dimensions

Set-up area, length:

Set-up area, width:

Set-up area, width:

Set-up area, height:

Required access area, length:

Required access area, width:

Required access area, height:

1880 mm

Required access area, height:

1882 mm

Tank/drain body

Distance pipe bottom outlet to tank bottom: 1350 mm
Distance pipe bottom inlet to tank bottom: 1420 mm
Outlet nominal size (OD): 250 mm
Outlet nominal size (DN): 250 mm



Inlet nominal size (OD): 250 mm Inlet nominal size (DN): 250 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: black

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 6200 l
Total volume: 11200 l
Contents of sludge trap: 5000 l
Storage quantity of grease: 2240 l

Control

Control unit: no